

SLA-1

Studio Linear Amplifier



Offering a superb level of sound quality, the SLA-1's clean and powerful circuitry combined with a straightforward user interface quickly and easily delivers the power you need for professional and project studio sound amplification. The SLA-1 has been designed for studio and even live applications, and has been engineered to provide excellent sound with ultra-low noise and distortion.

The SLA-1 has a long list of impressive features, including a Toroidal Transformer, XLR & 1/4" Inputs, Ground Lift Switch, SmartFan Silent Cooling Design, Power, Clip, Signal and Protect LED's, One IU Spacing and a frequency response of 10 Hz to 40 kHz.

The SLA-1 is rated at 100 watts rms/channel @ 8 ohms (130 watts rms/channel @ 4 ohms), hum and noise >100dB, input impedance of 22k ohm unbalanced (44k ohm balanced). It has an input sensitivity of 1V for rated power into 8 ohms, SmartFan Silent Cooling System and custom heat radiating fins. The SLA-1 is a powerful, compact amplifier that occupies 1 IU unit and weighs 6kg. Its rugged, steel chassis is designed for durable and reliable use.

The SLA-1 is perfect for pro, project and home studios, and is a perfect compliment to the new ART SLM-1 Studio Linear Monitors. The two together are a fantastic combination of both audio quality and of value!

SPECIFICATIONS:

Dimensions	1.75"H x 19.0"W x 9.5"D
Weight	13.2 lbs., 6.0kg.
Input Connections	XLR (balanced), 1/4" TRS (balanced/unbalanced)
Output Connections	Multi-Way Binding Posts
Input Impedance XLR, 1/4"	44k ohms (balanced), 22k ohms (unbalanced)
Input Sensitivity	1V for Full Power Output into 8 ohms
Stereo Output Power, 8 ohms	100 watts RMS per Channel
Stereo Output Power, 4 ohms	130 watts RMS per Channel
Bridged Output Power, 8 ohms	260 watts RMS mono
CMRR	>60dB (typical @1kHz)
Frequency Response	10Hz to 40kHz, +/- .5dB
Hum and Noise	>100dB below clipping
Total Harmonic Distortion (THD)	<0.05% (typical)
Transformer Type	Toroidal
Power Requirements	USA - 120vac 60 Hz 600 watts (max). Export units configured for country of destination.

APPLICATIONS:

Project, Home and Commercial Recording Studios, Broadcast/Radio/TV, Live Sound Systems/PA, Permanent/Fixed Installations, Church, Club and Practice PA Systems, DJ Sound Systems

Features and specifications subject to change without prior notice.
Copyright 2001 Applied Research and Technology.

APPLIED RESEARCH AND TECHNOLOGY, 215 TREMONT STREET, ROCHESTER, NY 14608 USA
Voice: 716/436.2720, Fax: 716/436.3942, <http://www.artproaudio.com>

ART
APPLIED RESEARCH AND TECHNOLOGY

FEATURES:

TOROIDAL TRANSFORMER

100 WATTS/
CHANNEL
@ 8 OHMS

260 WATTS/
BRIDGED
MONO @
8 OHMS

10 HZ to 40 KHZ
WITHIN 1dB

XLR & 1/4"
INPUTS

GROUND LIFT
SWITCH

SMARTFAN SILENT
COOLING SYSTEM

MULTI-WAY
BINDING POST
OUTPUTS

LOW PROFILE
1U RACK
MOUNTABLE
DESIGN

EXTREMELY LOW
NOISE, DISCRETE
LINEAR DESIGN

ALL STEEL
CHASSIS

PERFECT FOR
PROFESSIONAL
AND PROJECT
STUDIOS